

# F731E 35M IR Day/Night Outdoor IP Camera



- ▶ **Simultaneous MPEG-4 and Motion JPEG**
- ▶ **True day/night with automatic removable IR-cut filter**
- ▶ **Infrared LEDs with 35m effective range**
- ▶ **Power over Ethernet**

- Progressive scan CMOS
- Simultaneous MPEG-4 and Motion JPEG
- 30 frames per second in all resolutions
- 4.3mm, 6mm, 8mm, 12mm selectable lens
- True day/night capabilities with automatic removable IR-cut filter
- 850nm infrared LEDs with 35m effective range
- Two-way audio
- Power over Ethernet IEEE 802.3af
- 1 x alarm input, 1 x alarm output
- IP67 rated weatherproof housing
- SSL v3 advanced HTTPS encryption
- 3GPP mobile surveillance
- Easy access via Windows Live Messenger
- Multi-lingual user interface
- 16 channel surveillance software

**ZAVIG**

## Technical Specifications

<b>Models</b>	F731E
<b>Image sensor</b>	1/4" Progressive scan CMOS sensor
<b>Lens</b>	4.3, 6, 8, 12 mm (Selectable)
<b>Angle of view</b>	49°, 36°, 28°, 19° horizontal
<b>Digital Zoom</b>	10x digital
<b>Min Illumination</b>	0 Lux with IR
<b>IR working distance</b>	35 m
<b>IR LEDs</b>	8 φ IR LEDs x 36 (850nm)
<b>S/N Ratio</b>	50 dB
<b>Video</b>	Motion JPEG
<b>Compression</b>	MPEG-4 Part2 (ISO/IEC 14496-2), Profile: SP
<b>Resolutions</b>	Motion JPEG: 3 resolutions from 640x480 to 160x120 via API, 3 resolutions via configuration web page MPEG-4: 3 resolutions from 640x480 to 160x120 via API, 3 resolutions via configuration web page
<b>Frame rate</b>	Motion JPEG: Up to 15 fps at 640x480 (4:3 resolution) MPEG-4: Up to 30 fps at 640x480 (4:3 resolution)
<b>Video streaming</b>	Simultaneous Motion JPEG and MPEG-4 (Dual streaming) Controllable Frame rate and bandwidth Support Unicast and Multicast Support 3GPP/ISMA RTSP (Real Time Streaming Protocol)
<b>Image settings</b>	Rotation: Mirror, Flip, Mirror Flip brightness, contrast, saturation, hue Overlay capabilities: time, date, text and privacy image
<b>Shutter time</b>	1/7.5 ~ 1/120 sec.
<b>Audio</b>	Two-way (full duplex) External microphone input or line input Audio compression: G.711 PCM, 8kHz, 64 kbit/s
<b>Security</b>	Multiple user access levels with password protection, HTTPS encryption
<b>Users</b>	5 simultaneous users Unlimited number of users using multicast
<b>Alarm</b>	Alarm input 5V/12V DC
<b>Input/Output</b>	Alarm output Max 30W
<b>Instant</b>	Support MSN Live View
<b>Messenger</b>	

<b>Alarm and event management</b>	Input: alarm buffer, alarm input, motion detection Output: FTP, SMTP, HTTP event, alarm output Pre-and post alarm buffer
<b>Connectors</b>	RJ-45 for Ethernet 10/100 Base-T (with PoE) DC power jack Terminal blocks for 1 alarm input, 1 output Reset push switch 3.5 mm jack for Mic/Line, 3.5 mm jack for line out
<b>Casing</b>	Aluminum casing
<b>Power</b>	12V DC, 1A, Max 12W PoE (Power over Ethernet) Built-in IEEE 802.3af
<b>Operating conditions</b>	-30 ~ 50 °C (-22 ~ 122 °F) Humidity 20 ~ 80% RH (non-condensing)
<b>Installation, management, and maintenance</b>	ZAVIO Camera Management tool on CD and web-based configuration. Configuration of backup and restore Firmware upgrades over HTTP, firmware available at <a href="http://www.zavio.com">www.zavio.com</a>
<b>Minimum web browsing requirement</b>	Pentium 4 1.8GHz (or equivalent AMD) 64 MB RAM graphic cards (or equivalent on-board graphic cards) 512 MB RAM Windows 2000, 2003, XP or Vista Mac OS Leopard 10.5
<b>Supported protocols</b>	Bonjour, TCP/IP, DHCP, PPPoE, ARP, ICMP, FTP, SMTP, DNS, NTP, UPnP, RTSP, RTP, RTCP, HTTP, TCP, UDP, 3GPP/ISMA RTSP
<b>Included accessories</b>	Quick Installation Guide, CD (IP Surveillance Software, Intelligent IP Installer, User Manuals, and Language Pack), mounting and connector kits
<b>Video management software</b>	ZAVIO Intelligent IP Installer_ Video management software, for viewing, recording and archiving up to 16 cameras See <a href="http://www.zavio.com/support.htm">http://www.zavio.com/support.htm</a> for more software application
<b>Approvals</b>	CE, FCC, RoHS
<b>Dimensions (HxWxD) and weight</b>	265 x 85 (φ)mm (10.3" x 3.3") 1641.5 g (3.6 lb) excl. power supply

## Physical Description

